

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Express Mail Label No.: EL569253294US

Date of Deposit: September 8, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.


 Gary Paulazzo
SUPERCONDUCTING HEAT TRANSFER MEDIUM**RELATED APPLICATIONS**

5 This application relies upon the following for priority under 35 USC 120 or 371: U.S. Provisional Applications Ser. Nos. 60/029,266, filed 10/25/96 and 60/036,043, filed 036,043; PCT US/18,876, filed 10/24/97; and U.S. Patent Applications Ser. Nos. 08/957,148, filed 10/24/97 and 09/437,659, filed 11/10/99, the latter of which are co-pending.

TECHNICAL FIELD

10 The present invention relates generally to the field of heat transfer. More particularly, the present invention relates to a superconducting heat transfer medium which is disposed within a conduit to rapidly and efficiently transfer heat.

BACKGROUND ART

15 Efficiently transporting heat from one location to another always has been a problem. Some applications, such as keeping a semiconductor chip cool, require rapid transfer and removal of heat, while other applications, such as dispersing heat from a furnace, require rapid transfer and retention of heat. Whether removing or retaining heat, the heat transfer conductivity of the material utilized limits the efficiency of the heat transfer. Further, when heat retention is desired, heat losses to the environment further reduce the efficiency of the heat transfer.

20 For example, it is well known to utilize a heat pipe for heat transfer. The heat pipe operates on the principle of transferring heat through mass transfer of a fluid carrier contained therein and phase change of the carrier from the liquid state to the

vapor state within a closed circuit pipe. Heat is absorbed at one end of the pipe by vaporization of the carrier and released at the other end by condensation of the carrier vapor. Although the heat pipe improves thermal transfer efficiency as compared to solid metal rods, the heat pipe requires the circulatory flow of the liquid/vapor carrier and is limited by the association temperatures of vaporization and condensation of the carrier. As a result, the heat pipe's axial heat conductive speed is further limited by the amount of latent heat of liquid vaporization and on the speed of circular transformation between liquid and vapor states. Further, the heat pipe is convectional in nature and suffers from thermal losses, thereby reducing the thermal efficiency.

An improvement over the heat pipe, which is particularly useful with nuclear reactors, is described by Kurzweg in U.S. Patent Number 4,590,993 for a Heat Transfer Device For The Transport Of Large Conduction Flux Without Net Mass Transfer. This device has a pair of fluid reservoirs for positioning at respective locations of differing temperatures between which it is desired to transfer heat. A plurality of ducts having walls of a material which conducts heat connect the fluid reservoirs. Heat transfer fluid, preferably a liquid metal such as mercury, liquid lithium or liquid sodium, fills the reservoirs and ducts. Oscillatory axial movement of the liquid metal is created by a piston or a diaphragm within one of the reservoirs so that the extent of fluid movement is less than the duct length. This movement functions to alternately displace fluid within the one reservoir such that the liquid metal is caused to move axially in one direction through the ducts, and then to in effect draw heat transfer fluid back into the one reservoir such that heat transfer fluid moves in the opposite direction within the ducts. Thus, within the ducts, fluid oscillates in alternate axial directions at a predetermined frequency and with a predetermined tidal displacement or amplitude. With this arrangement, large quantities of heat are transported axially along the ducts from the hotter reservoir and transferred into the walls of the ducts, provided the fluid is oscillated at sufficiently high frequency and with a sufficiently large tidal displacement. As the fluid

oscillates in the return cycle to the hotter reservoir, cooler fluid from the opposite reservoir is pulled into the ducts and the heat then is transferred from the walls into the cooler fluid. Upon the subsequent oscillations, heat is transferred to the opposite reservoir from the hotter reservoir. However, as with the heat pipe, this device is limited in efficiency by the heat transfer conductivity of the materials comprising the reservoirs and ducts and by heat losses to the atmosphere.

It is known to utilize radiators and heat sinks, to remove excess heat generated in mechanical or electrical operations. Typically, a heat transferring fluid being circulated through a heat generating source absorbs some of the heat produced by the source. The fluid then is passed through tubes having heat exchange fins to absorb and radiate some of the heat carried by the fluid. Once cooled, the fluid is returned back to the heat generating source. Commonly, a fan is positioned to blow air over the fins so that energy from the heat sink radiates into the large volume of air passing over the fins. With this type of device, the efficiency of the heat transfer is again limited by the heat transfer conductivity of the materials comprising the radiator or the heat sink.

Dickinson in U.S. Patent Number 5,542,471 describes a Heat Transfer Element Having Thermally Conductive Fibers that eliminates the need for heat transferring fluids. This device has longitudinally thermally conductive fibers extended between two substances that heat is to be transferred between in order to maximize heat transfer. The fibers are comprised of graphite fibers in an epoxy resin matrix, graphite fibers cured from an organic matrix composite having graphite fibers in an organic resin matrix, graphite fibers in an aluminum matrix, graphite fibers in a copper matrix, or a ceramic matrix composite.

In my People's Republic of China Patent Number 89108521.1, I disclosed an Inorganic Medium Thermal Conductive Device. This heat conducting device greatly improved the heat conductive abilities of materials over their conventional state. Experimentation has shown this device capable of transferring heat along a sealed

metal shell having a partial vacuum therein at a rate of 5,000 meters per second. On the internal wall of the shell is a coating applied in three steps having a total optimum thickness of 0.012 to 0.013 millimeters. Of the total weight of the coating, strontium comprises 1.25%, beryllium comprises 1.38%, and sodium comprises 1.95%. This heat conducting device does not contain a heat generating powder and does not transfer heat nor prevent heat losses to the atmosphere in a superconductive manner as the present invention.

BRIEF SUMMARY OF THE INVENTION

It is generally accepted that when two substances having different temperatures are brought together, the temperature of the warmer substance decreases and the temperature of the cooler substance increases. As the heat travels along a heat conducting conduit from a warm end to a cool end, available heat is lost due to the heat conducting capacity of the conduit material, the process of warming the cooler portions of the conduit and thermal losses to the atmosphere. In accordance with the present invention and these contemplated problems which continue to exist in this field, one objective of this invention is to provide a superconducting heat transfer medium that is environmentally sound, rapidly conducts heat and preserves heat, in a highly efficient manner. Further, the present invention does not require a tightly controlled process environment to produce.

Another object of this invention is to provide a device that conducts heat with a heat preservation efficiency approaching 100 percent.

Also, another object of this invention is to provide a method for denaturation of rhodium and radium carbonate.

Yet another objective of this invention is to provide a process for making a device that transfers heat from a heat source from one point to another without any effective heat loss.

Still yet, another object of this invention is to provide a heat sink utilizing the superconducting heat transfer medium that rapidly and efficiently disperses heat from a heat generating object.

This invention accomplishes the above and other objectives and overcomes the disadvantages of the prior art by providing a superconducting heat transfer medium that is relatively inexpensive to prepare, simple in design and application, and easy to use.

The medium is applied to the conduit in three basic layers. The first two layers are prepared from solutions which are exposed to the inner wall of the conduit. Initially, the first layer, which primarily comprises in ionic form various combinations of sodium, beryllium, a metal such as manganese or aluminum, calcium, boron, and dichromate radical, is absorbed into the inner wall of the conduit to a depth of 0.008 mm to 0.012 mm. Subsequently, the second layer, which primarily comprises in ionic form various combinations of cobalt, manganese, beryllium, strontium, rhodium, copper, β -titanium, potassium, boron, calcium, a metal such as aluminum and the dichromate radical, builds on top of the first layer and actually forms a film having a thickness of 0.008 mm to 0.012 mm over the inner wall of the conduit. Finally, the third layer is a powder comprising various combinations of rhodium oxide, potassium dichromate, radium oxide, sodium dichromate, silver dichromate, monocrystalline silicon, beryllium oxide, strontium chromate, boron oxide, β -titanium and a metal dichromate, such as manganese dichromate or aluminum dichromate, that evenly distributes itself across the inner wall. The three layers can be applied to a conduit and then heat polarized to form a superconducting heat transfer device that transfers heat without any net heat loss, or can be applied to a pair of plates having a small cavity relative to a large surface area to form a heat sink that can immediately disperse heat from a heat source.

It is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such,

those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods, and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

Other objects, advantages and capabilities of the invention will become apparent from the following description taken in conjunction with the accompanying drawings showing the preferred embodiment of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood and the above objects as well as objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

Figure 1 is a perspective view of a superconducting heat transfer device made in accordance with the present invention;

Figure 2 is a cross-sectional view of the device of Figure 1;

Figure 3 is a perspective view of a plug used with the device of Figure 1;

Figure 4 is a perspective view of a heat sink made in accordance with the present invention;

Figure 5 is a side elevation view of the heat sink of Figure 4;

Figure 6 is a cross-sectional view of the heat sink of Figure 4;

Figure 7 is an example testing apparatus for testing the superconducting heat transfer device;

Figure 8 is the data from the results of Test No. 1 on a preferred embodiment of the present invention;

Figure 9 is the data from the results of Test No. 2 on a preferred embodiment of the present invention;

Figure 10 is the data from the results of Test No. 3 on a preferred embodiment of the present invention; and

Figure 11 is the data from the results of Test No. 4 on a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

For a fuller understanding of the nature and desired objects of this invention, reference should be made to the following detailed description taken in connection with the accompanying drawings. Referring to the drawings, wherein like reference numerals designate corresponding parts throughout the several figures, reference is made first to Figures 1 and 2. A superconducting heat transfer device 2 comprising a carrier such as conduit 4 containing a superconducting heat transfer medium 6 is provided which can be placed within a cavity 8 of the conduit 4 without regard to the material comprising the conduit 4. While the conduit 4 shown in Figure 1 is cylindrical in shape, the present invention envisions conduits in a variety of shapes and sizes. The resulting heat transfer capabilities of the medium 6 bearing conduit 4 are greatly enhanced without any subsequent thermal loss. If properly applied within conduit 4, medium 6 actually is catalyzed by heat to become a heat generator itself. Medium 6 is activated at a temperature of about 38 °C and can operate to a maximum temperature of about 1730 °C. Although not completely certain, it is believed that the thermal generating capability of medium 6 is directly related to mass loss of medium 6 after activation. Because medium 6 is capable of immediately transferring heat through conduit 4 from a heat source (not shown), conduit 4 can be exposed to and operate within an environment having a source temperature far in excess of the melting temperature of the untreated material comprising conduit 4.

It is additionally believed that during the initial stages of medium 6 activation, medium 6 reacts endothermically. As a result, medium 6 can immediately absorb available heat from the heat source and thereafter immediately transfer the heat throughout conduit 4. If the cubic volume of cavity 8 is small in relation to external surface 10 area of conduit 4, as shown in Figures 4 through 6, medium 6 absorbs heat to provide a heat sink 12 which immediately removes heat from the heat generating source. Heat radiation is directly related to heat capacity, the rate of heat conduction, and thermal conductivity. This, in other words, determines the speed (rate) at which the volume (quantity) of heat can be transferred in each unit volume.

If conduit 4 or carrier has a small cavity in relation to a large external surface 10 area, the carrier is more capable of distributing heat across the external surface 10. In applications where the temperature of the heat generating source does not exceed 38 °C, the medium 6 activation temperature, the heat is immediately absorbed and dispersed by medium 6. In cases where the heat generating source exceeds 38 °C, heat sink 12 is still highly effective because of the ability of medium 6 to rapidly transfer the heat to heat sink external surface 14 and be efficiently dispersed to the atmosphere by thermal radiation.

Medium 6 is applied in three basic layers, the first two of which are prepared from solutions. Each solution is exposed sequentially to an inner conduit surface 16 or an inner heat sink surface 18. Initially, first layer 20 is absorbed into inner conduit surface 16 or heat sink surface 18. Subsequently, second layer 22 builds on top of first layer 20 and actually forms a film over inner conduit surface 16 or heat sink surface 18. Finally, third layer 24 is a powder that evenly distributes itself across inner conduit surface 16 or heat sink surface 18. Although reference is made to conduit 4 below in the discussion of medium 6, the application of medium 6 within heat sink 12 is the same.

First layer 20 is an anti-corrosion layer which prevents etching of inner conduit surface 16 and, in theory, causes a realignment of the atomic structure of

conduit 4 material so that heat is more readily absorbed. A further function of first layer 20 is to prevent inner conduit surface 16 from producing oxides. For example, ferrous metals can be easily oxidized when exposed to water molecules contained in the air. The oxidation of inner conduit surface 16 will cause corrosion and also create a heat resistance. As a result, there is an increased heat load while heat energy is transferred within conduit 4, thus causing an accumulation of heat energy inside conduit 4. Should this occur, the life span of medium 6 is decreased.

Next, second layer 22, the active layer, prevents the production of elemental hydrogen and oxygen, thus restraining oxidation between oxygen atoms and the material of conduit 4 (or carrier). Also in theory, second layer 22 conducts heat across inner conduit surface 16 comparably to that of electricity being conducted along a wire. Experimentation has found that heat can be conducted by medium 6 at a rate of 15,000 meters per second, regardless of the heat conductivity coefficient of the material of the conduit. Second layer 22 also assists in accelerating molecular oscillation and friction associated with third layer 24 to provide a heat transfer pathway for heat conduction.

Third layer 24 is referred to, due to its color and appearance, as the "black powder" layer. It is believed third layer 24 generates heat once medium 6 is exposed to the minimum activation temperature of 38 °C. Upon activation of medium 6, the atoms of third layer 24, in concert with first layer 20 and second layer 22, begin to oscillate. As the heat source temperature increases, it is believed that frequency of oscillation increases. It is believed that when the activating temperature reaches 200 °C, the frequency of oscillation is 230 million times per second, and when the activating temperature is higher than 350 °C, the frequency can even reach 280 million times per second. Theoretically, the higher the activating temperature, the higher the frequency of oscillation. Therefore it is suspected that the higher the load, the higher the performance efficiency of the conduit. During the heat transfer process, there is neither phase transition nor mass transfer of medium 6.

Experimentation has shown that a steel conduit 4 with medium 6 properly disposed therein has a thermal conductivity that is generally 20,000 times higher than the thermal conductivity of silver, and can reach under laboratory conditions a thermal conductivity that is 30,000 times higher than the thermal conductivity of silver.

5 During use, after activation, medium 6 loses mass with use (decay caused by the conversion of mass into energy). As a result, medium 6 has a long, but limited useful life. Tests have shown that after 110,000 hours of continuous use, both the amount of medium 6 and the molecule vibration frequency remain the same as from the initial activation. However, at 120,000 hours of continuous use, the amount
10 (mass) of medium 6 starts to decline at a rate of about 0.5% every 32 hours with the molecule vibration frequency significantly decreased by about 6%. After about 123,200 hours of continuous use, medium 6 became ineffective. It is believed that the aging is caused mainly by the decay, or conversion of mass into energy, of third layer 24. As is expected, lower working temperatures slow the decay of third layer
15 24. First layer 20 and second layer 22 have been determined to be used up at a rate of approximately 0.001 mm per 10,000 hours of use.

To prepare first layer 20, a first layer solution is manufactured and thereafter applied to inner conduit surface 16. A representative first layer solution is manufactured by the following steps, preferably conducted in the order of listing:

- 20 (a) placing 100 ml of distilled water into an inert container such as glass or, preferably, ceramic;
- (b) dissolving and mixing between 2.0 and 5.0 grams of sodium peroxide into the water;
- (c) dissolving and mixing between 0.0 and 0.5 grams of sodium oxide into
25 the solution of step (b);
- (d) dissolving and mixing between 0.0 and 0.5 grams of beryllium oxide into the solution of step (c);

(e) dissolving and mixing between 0.3 and 2.0 grams of a metal dichromate such as aluminum dichromate or, preferably, magnesium dichromate into the solution of step (d);

5 (f) dissolving and mixing between 0.0 and 3.5 grams of calcium dichromate into the solution of step (e); and

(g) dissolving and mixing between 1.0 and 3.0 grams of boron oxide into the solution of step (f) to form the first layer solution.

10 It is preferred for steps (a) through (g) to be conducted in the order listed and under conditions having a temperature between 0 °C and 30 °C, preferably 5 °C to 8 °C, and a relative humidity of no greater than 40%. The steps for the addition of beryllium oxide and the metal dichromate can be reversed in order so that the metal dichromate is added to the first layer solution prior to the addition of beryllium oxide without causing negative effects. When medium 6 contains manganese sesquioxide, rhodium oxide or radium oxide, either sodium peroxide or sodium oxide may be
15 eliminated, but the resulting heat transfer efficiency of medium 6 will be lower and the life span of medium 6 will be reduced by approximately 1 year. As to the remaining components of the first layer solution and subject to the above exceptions, each component should be added in the order presented. If the components of the first layer solution are combined in an order not consistent with the listed sequence,
20 the solution can become unstable and may result in a catastrophic reaction.

Prior to manufacturing a solution for second layer 22 and compiling the compounds for third layer 24, rhodium and radium carbonate undergo a denaturation process. To denature 100 grams of rhodium powder, blend 2 grams of pure lead powder with the rhodium powder within a container and subsequently place the
25 container with the rhodium and lead powders into an oven at a temperature of 850 °C to 900 °C for at least 4 hours to form rhodium oxide. Then separate the rhodium oxide from the lead. To denature 100 gram of radium carbonate powder, blend 11 grams of pure lead powder with the radium carbonate within a container and

subsequently place the container with the radium carbonate and lead powders into an oven at a temperature of 750 °C to 800 °C for at least eight hours to form radium oxide. During experimentation, a platinum container was utilized in the denaturation process. The material comprising the container should be inert with respect to rhodium, rhodium oxide, radium carbonate, radium oxide, and lead. Lead utilized in the denaturation process preferably should be 99.9% pure and can be recycled for subsequent use in further like denaturation processes. Subsequent testing of medium 6 at a resting state and an active state with a PDM personal dosimeter resulted in no radioactive emissions of any kind detectable over background radiation.

An isotope of titanium is utilized in medium 6. In some countries the isotope is known as B-type titanium, and in the United States of America, the isotope is known as β -titanium.

Second layer 22 is derived from a solution that is applied to inner conduit surface 16 over first layer 20. Similar to the first layer solution, a representative second layer solution is manufactured by the following steps, conducted preferably in the order of listing:

- (a) placing 100 ml of twice-distilled water into an inert container such as glass or, preferably, ceramic;
- (b) dissolving and mixing between 0.2 and 0.5 grams of cobaltous, oxide into the twice-distilled water;
- (c) dissolving and mixing between 0.0 and 0.5 grams of manganese sesquioxide into the solution of step (b);
- (d) dissolving and mixing between 0.0 and 0.01 grams of beryllium oxide into the solution of step (c);
- (e) dissolving and mixing between 0.0 and 0.5 grams of strontium chromate into the solution of step (d);
- (f) dissolving and mixing between 0.0 and 0.5 grams of strontium carbonate into the solution of step (e);

(g) dissolving and mixing between 0.0 and 0.2 grams of rhodium oxide into the solution of step (f);

(h) dissolving and mixing between 0.0 and 0.8 grams of cupric oxide into the solution of step (g);

5 (i) dissolving and mixing between 0.0 and 0.6 grams of β -titanium. into the solution of step (h);

(j) dissolving and mixing between 1.0 and 1.2 gram of potassium dichromate into the solution of step (i);

10 (k) dissolving and mixing between 0.0 and 1.0 gram of boron oxide into the solution of step (j);

(l) dissolving and mixing between 0.0 and 1.0 grams of calcium dichromate into the solution of step (k); and

15 (m) dissolving and mixing between 0.0 and 2.0 grams of aluminum dichromate or, preferably, magnesium dichromate, into the solution of step (l) to form the second layer solution.

20 It is preferred for the twice-distilled water to have an electrical conductivity that approaches 0. The higher the electrical conductivity, the greater the problem of static electricity interfering with medium 6 and causing a reduction in the thermal conductive efficiency. The steps of (a) through (m) preferably are conducted under conditions having a temperature between 0 °C and 30 °C and a relative humidity of no greater than 40%. When medium 6 contains rhodium oxide or radium oxide, the amount of manganese sesquioxide may be reduced or eliminated; however, the life span of medium 6 will be reduced and the thermal conductive efficiency will be reduced by approximately 0.2%. Generally, β -titanium may be added to the second layer solution at any step listed above, except that it should not be added to the twice-distilled water at step (b) or as the last component of the solution. Adding β -titanium at step (b) or as the last component of the solution can cause instability of the second layer solution. The steps for adding manganese sesquioxide and beryllium oxide may

25

be reversed in order so that beryllium oxide is added to the second layer solution prior to the addition of manganese sesquioxide. Likewise, the steps for adding potassium dichromate and calcium dichromate may be reversed in order so that calcium dichromate is added to the second layer solution prior to the addition of potassium dichromate. If the components of the second layer solution are combined in an order not consistent with the listed sequence and the exceptions noted above, the solution can become unstable and may result in a catastrophic reaction.

Prior to preparing third layer 24, silicon is treated by magnetic penetration. Monocrystalline silicon powder having a preferred purity of 99.999% is placed within a non-magnetic container and disposed within a magnetic resonator for at least 37 minutes, preferably 40 minutes to 45 minutes. The magnetic resonator utilized during experimentation was a 0.5 kilowatt, 220 volt and 50 hertz magnetic resonator. If the silicon being used has a purity lower than 99.999%, the amount of silicon needed in third layer 24 increases. The magnetic resonator is used to increase the atomic electron layer of the silicon, which in turn, increases the speed that heat is conducted by medium 6.

A representative powder of third layer 24 is manufactured by the following steps, conducted preferably in the order of listing:

- (a) placing between 0.0 and 1.75 gram of denatured rhodium oxide into an inert container such as glass or, preferably, ceramic;
- (b) blending between 0.3 and 2.6 grams of sodium dichromate with the rhodium oxide;
- (c) blending between 0.0 and 0.8 grams of potassium dichromate with the mixture of step (b);
- (d) blending between 0.0 and 3.1 grams of denatured radium oxide with the mixture of step (c);
- (e) blending between 0.1 and 0.4 gram of silver dichromate with the mixture of step (d);

(f) blending between 0.2 and 0.9 grams of the monocrystalline silicon powder treated by magnetic penetration with the mixture of step (e);

(g) blending between 0.0 and 0.01 grams of beryllium oxide with the mixture of step (f);

5 (h) blending between 0.0 and 0.1 gram of strontium chromate with the mixture of step (g);

(i) blending between 0.0 and 0.1 grams of boron oxide with the mixture of step (h);

10 (j) blending between 0.0 and 0.1 gram of sodium peroxide with the mixture of step (i);

(k) blending between 0.0 and 1.25 grams of β -titanium with the mixture of step (j); and

15 (l) blending between 0.0 and 0.2 grams of aluminum dichromate or, preferably, magnesium dichromate, into the mixture of step (k) to form the third layer powder.

The powder for third layer 24 preferably should be blended at a temperature lower than about 25 °C. By blending at lower temperatures, the heat conducting efficiency of medium 6 improves. Further, the relative humidity should be below 40%. It is preferred for the relative humidity to be between 30% and 35%.

20 Generally, radium oxide and β -titanium may be added to the powder of third layer 24 at any step listed above, except that neither one should be added to the powder as the first or last component. Adding either radium oxide or β -titanium as the first or last component of the powder can cause instability of medium 6 and may result in a catastrophic reaction. The steps for adding potassium dichromate and silver
25 dichromate may be reversed in order so that silver dichromate is added to the powder of third layer 24 prior to the addition of potassium dichromate. Likewise, the steps for adding strontium chromate and beryllium oxide may be reversed in order so that beryllium oxide is added to the powder of third layer 24 prior to the addition of

strontium chromate. If the components of the powder of third layer 24 are combined in an order not consistent with the listed sequence and the exceptions noted above, medium 6 can become unstable and may result in a catastrophic reaction.

5 The powder of third layer 24 may be stored for prolonged periods of time. To prevent degradation by light and humidity, the powder of third layer 24 should be stored in a dark, hermetic storage container made from an inert material preferably glass. A moisture absorbing material also may be placed within the storage container so long as the moisture absorbing material is inert to and is not intermingled with the powder of third layer 24.

10 Once the solutions for first layer 20 and second layer 22 and the powder of third layer 24 are prepared, the superconducting heat transfer device 2 can be fabricated. Conduit 4 can be any one of a variety of metallic or non-metallic materials; and in any event, should have very little oxidation, preferably no oxidation, on inner conduit surface 16. It is recommended for conduit 4, particularly if conduit 15 4 is manufactured of a metal, to be clean, dry and free of any oxides or oxates. This can be accomplished by convectional treating by, for example, sand blasting, weak acid washing, or weak base washing. Any materials used to clean and treat conduit 4 should be completely removed and inner conduit surface 16 also should be dry prior to adding medium 6 to conduit 4. Additionally, the wall thickness of conduit 4 20 should be selected to take a wear rate of at least 0.1 mm per year into account. This wearing is caused by the oscillation of third layer's 24 molecules. For steel, the wall thickness should be at least 3 mm. Obviously, softer materials need to be thicker. The conduit 4 may be of considerable length. In fact, it has been found that the performance efficiency of the conduit 4 increases with length.

25 A representative superconducting heat transfer device 2 is manufactured utilizing the following steps:

- (a) placing the first layer solution into a first layer solution container;

(b) submerging conduit 4 having cavity 8 within the first layer solution such that the first layer solution fills cavity 8, conduit 4 preferably having a non-horizontal placement with lower end 26 disposed in a downward direction within the first layer solution, at a temperature between 0 °C and 30 °C for at least 8 hours so that the first layer solution can penetrate the wall of conduit 4 to a depth of between 0.008 mm and 0.012 mm;

(c) drying conduit 4 naturally at ambient conditions to form first layer 20 within cavity 8;

(d) placing the second layer solution into a second layer solution container;

(e) submerging conduit 4 with first layer 20 within the second layer solution such that the second layer solution fills cavity 8, conduit 4 preferably having a non-horizontal placement with lower end 26 disposed in a downward direction within the second layer solution at a temperature between 55 °C and 65 °C, preferably 60 °C, for at least 4 hours;

(f) drying conduit 4 naturally at ambient conditions to form within cavity 8 a film of second layer 22 having a thickness between 0.008 mm and 0.012 mm;

(g) welding an end cap 28 on the opposite end of conduit 8 from lower end 26 by a precision welding technique, preferably heli-arc welding done in the presence of helium or argon;

(h) welding an injection cap 30 having a bore 32 with a diameter between 2.4 mm and 3.5 mm, preferably 3.0 mm, on lower end 26 preferably by the method utilized in step (g);

(i) heating lower end 26 to a temperature not to exceed 120 °C, preferably to about 40 °C;

(j) injecting the powder of third layer 24 through bore 32 in an amount of at least 1 cubic meter per 400,000 cubic meters of cavity 8 volume;

(k) inserting plug 34, preferably conical-shaped and solid, as shown in Figure 3, into bore 32;

(l) heating lower end 26 to a temperature between 80 °C and 125 °C;

(m) removing plug 34 from bore 32 for no more than about 3 seconds, preferably about 2 seconds, and reinserting plug 34 into bore 32; and

(n) sealing plug 34 within bore 32, preferably by the welding method utilized in step (g), to form the superconducting heat transfer device 2.

If the temperature of lower end 26 in step (i) exceeds 60 °C, lower end 26 should be allowed to cool to at least 60 °C prior to injecting the powder of third layer 24 into cavity 8. By following the steps above, lower end 26 becomes heat polarized. In other words, lower end 26 is polarized to receive heat from the heat source and transfer the heat away from lower end 26.

The purpose of removing plug 34 from bore 32 in step (m) above is to release air and water molecules from cavity 8 of conduit 4 to the outside environment. A blue gas has been observed exiting bore 32 once plug 34 is removed. However, if a blue light is observed emitting from bore 32 prior to plug 34 being reinserted into bore 32, the powder of third layer 24 has escaped to the atmosphere and steps (j) through (m) need to be repeated. If step (j) can be accomplished in a humidity free environment under a partial vacuum, steps (l) and (m) can be eliminated, but it is not recommended.

Manganese sesquioxide, rhodium oxide, and radium oxide are not needed in all applications of medium 6. These three components are used in medium 6 when the superconducting heat transfer device 2 is exposed to an environment of high pressure steam and conduit 4 is manufactured of high carbon steel. In this special case, high pressure is defined as being 0.92 million pascals or higher. Manganese sesquioxide, rhodium oxide, and radium oxide are not needed and may be eliminated from medium 6 when the use of the superconducting heat transfer device 2 is not in a high pressure steam environment, even if conduit 4 is made of high carbon steel.

Additionally, when manganese sesquioxide, rhodium oxide, and radium oxide are eliminated from medium 6, the powder of third layer 24 should be provided in an amount of 1 cubic meter of third layer powder per 200,000 cubic meters of cavity 8 volume.

5 As disclosed above, heat sink 12 utilizes superconducting heat transfer medium 6. A representative heat sink 12 is manufactured utilizing the following steps:

(a) placing the first layer solution into a first layer solution container;
 (b) submerging first plate 36 and second plate 38 within the first layer
 10 solution such that the first layer solution covers at least one side of each of first plate 36 and second plate 38 at a temperature between 0 °C and 30 °C for at least 8 hours so that the first layer solution can penetrate the first layer solution covered side 40 to a depth between 0.008 mm and 0.012 mm, first plate 36 and second plate 38 having mating edges 42 and form a relatively small volume cavity 8 with respect to the
 15 surface area of first plate 36 and second plate 38 when first plate 36 and second plate 38 are placed together, and at least one of first plate 36 and second plate 38 has an opening 44 between 2.4 mm and 3.5 mm, preferably 3.0 mm;

(c) drying first plate 36 and second plate 38 naturally at ambient
 conditions to form first layer 20 on the first layer covered sides 40 of first plate 36
 20 and second plate 38;

(d) placing the second layer solution into a second layer solution container;

(e) submerging first plate 36 and second plate 38 within the second layer
 solution such that the second layer solution contacts first layer 20 at a temperature
 25 between 55 °C and 65 °C, preferably 60 °C, for at least 4 hours;

(f) drying first plate 36 and second plate 38 naturally at ambient
 conditions to form the film of second layer 22 having a thickness between 0.008 mm
 and 0.012 mm on first layer 20;

(g) welding first plate 36 and second plate 38 together along mating edges 42 by a precision welding technique, preferably heli-arc welding done in the presence of helium or argon, so that the first layer covered sides 40 face one another;

(h) injecting the powder of third layer 24 into cavity 8 through opening 44 in an amount of at least 1 cubic meter per 400,000 cubic meters of cavity volume; and

(i) sealing opening 44 preferably by the method utilized in step (g) to form heat sink 12.

Heat sink 12 can be manufactured in the same manner as superconducting heat transfer device 2; that is, heat sink 12 may be heat polarized, but it is not necessary. Also, the steps calling for welding in the manufacture of superconducting heat transfer device 2 and heat sink 12 can be accomplished by using glues, adhesives and/or epoxies, preferably heat tolerant glues, adhesives and epoxies. Additionally, all welding should be conducted to a depth of two-thirds of the thickness of conduit 4, end cap 28, injection cap 30, first plate 36 or second plate 38. After welding, a leakage test, such as the Helium Vacuum Leakage Test, should be performed.

All materials comprising conduit 4, end cap 28, injection cap 30 and plug 34 of superconducting heat transfer device 2 or first plate 36 and second plate 38 of heat sink 12 should be compatible with one another. This prevents problems, particularly material fractures, associated with the different expansion/contraction rates of different materials used in combination and corrosion associated with anodic reactions. The material selected also should be compatible with and able to withstand the external environment in which superconducting heat transfer device 2 or heat sink 12 operates. For example, if superconducting heat transfer device 2 is operating in an acidic environment, the material should be resistant to the acid present.

The invention will be better understood by reference to the following illustrated examples. With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the invention, to include variations in size, materials, shape, form, function and manner of operation, assembly

and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those described in the specification are intended to be encompassed by the present invention.

The super conducting heat transfer medium 6 can also conduct cold temperature transfer when a cold source is exposed to either end of the conduit 4. Cold temperatures have been successfully transferred across the conduit 4 when one end thereof came in contact with liquid nitrogen having a temperature of -195 degrees C.

The following examples describe various compositions of first layer 20, second layer 22 and third layer 24 and are known to be useful in preparing superconducting heat transfer device 2 or heat sink 12. The components preferably are added to the respective layers 20, 22, 24 in the amounts listed, in the order of listing and in accordance with the respective steps described above.

Example 1

For forming first layer 20, into 100 ml of distilled water add 5.0 grams of sodium peroxide, 0.5 gram of sodium oxide, 2.0 grams of magnesium dichromate or aluminum dichromate, 2.5 grams of calcium dichromate and 3.0 grams of boron oxide.

For forming second layer 22, into 100 ml of twice-distilled water add 0.5 gram of cobaltous oxide, 0.5 gram of manganese sesquioxide, 0.5 gram of strontium carbonate, 0.2 gram of rhodium oxide, 0.8 gram of cupric oxide, 0.6 gram of β -titanium and 1.2 gram of potassium dichromate.

For forming the powder of third layer 24, combine 1.75 grams of rhodium oxide, 1.25 gram of β -titanium, 3.1 grams of radium oxide, 2.6 gram of sodium dichromate, 0.4 gram of silver dichromate and 0.9 gram of monocrystalline silicon powder.

Example 2

For forming first layer 20, into 100 ml of distilled water add 5.0 gram of sodium peroxide, 0.5 gram of beryllium oxide, 2.0 grams of magnesium dichromate, 2.0 grams of calcium dichromate and 3.0 grams of boron oxide.

5 For forming second layer 22, into 100 ml of twice-distilled water add 0.5 gram of cobaltous oxide, 0.5 gram of strontium chromate, 0.8 gram of cupric oxide, 0.6 gram of β -titanium and 1.2 gram of potassium dichromate.

10 For forming the powder of third layer 24, combine 1.6 grams of sodium dichromate, 0.8 gram of potassium dichromate, 0.4 gram of silver dichromate and 0.9 gram of monocrystalline silicon powder.

Example 3

15 For forming first layer 20, into 100 ml of distilled water add 5.0 grams of sodium peroxide, 0.5 gram of beryllium oxide, 2.0 grams of magnesium dichromate, 3.5 grams of calcium dichromate and 3.0 grams of boron oxide.

For forming second layer 22, into 100 ml of twice-distilled water add 0.5 gram of cobaltous oxide, 0.5 gram of strontium chromate, 0.8 gram of cupric oxide, 0.6 gram of β -titanium and 1.2 grams of potassium dichromate.

20 For forming the powder of third layer 24, combine 1.6 grams of sodium dichromate, 0.8 gram of potassium dichromate, 0.6 gram of silver dichromate and 0.9 gram of monocrystalline silicon powder.

Example 4

25 For forming first layer 20, into 100 ml of distilled water add 2.0 grams of sodium peroxide, 0.3 gram of beryllium oxide, 2.0 grams of magnesium dichromate, and 1.0 gram of boron oxide.

For forming second layer 22, into 100 mm of twice-distilled water add 0.5 gram of cobaltous oxide, 0.5 gram of strontium chromate, 0.4 gram of β -titanium and 1.0 gram of potassium dichromate.

For forming the powder of third layer 24, combine 0.5 gram of sodium dichromate, 0.8 gram of potassium dichromate, 0.1 gram of silver dichromate, 0.3 gram of monocrystalline silicon powder, 0.01 gram of beryllium oxide, 0.1 gram of strontium chromate, 0.1 gram of boron oxide and 0.1 gram of sodium peroxide.

Example 5

For forming first layer 20, into 100 ml of distilled water add 2.0 grams of sodium peroxide, 0.3 gram of beryllium oxide, 2.0 grams of magnesium dichromate and 1.0 gram of boron oxide.

For forming second layer 22, into 100 ml of twice-distilled water add 0.3 gram of cobaltous oxide, 0.3 gram of strontium chromate, 1.0 gram of potassium dichromate and 1.0 gram of calcium dichromate.

For forming the powder of third layer 24, combine 0.3 gram of sodium dichromate, 0.1 gram of silver dichromate, 0.8 gram of potassium dichromate, 0.2 gram of monocrystalline silicon powder, 0.01 gram of beryllium oxide, 0.1 gram of strontium chromate, 0.1 gram of boron oxide, 0.2 gram of β -titanium and 0.1 gram of sodium peroxide.

Example 6

For forming first layer 20, into 100 ml of distilled water add 2.0 grams of sodium peroxide, 0.3 gram of magnesium dichromate, 1.0 gram of boron oxide and 1.0 gram of calcium dichromate.

For forming second layer 22, into 100 ml of twice-distilled water add 0.3 gram of cobaltous oxide, 0.01 gram of beryllium oxide, 1.0 gram of potassium dichromate, 1.0 gram of boron oxide and 2.0 grams of magnesium dichromate.

For forming the powder of third layer 24, combine 0.3 gram of sodium dichromate, 0.1 gram of silver dichromate, 0.8 gram of potassium dichromate, 0.2 gram of monocrystalline silicon powder, 0.1 gram of strontium chromate, 0.01 gram of beryllium oxide, 0.1 gram of boron oxide, 0.1 gram of sodium peroxide, 0.2 gram of β -titanium and 0.2 gram of magnesium dichromate.

Example 7

For forming first layer, into 100 ml of distilled water add 2.0 grams of sodium peroxide, 0.3 gram of magnesium dichromate and 1.0 gram of boron oxide.

For forming second layer 22, into 100 ml of twice-distilled water add 0.2 gram of cobaltous oxide, 1.0 gram of calcium dichromate, 1.0 gram of potassium dichromate, 0.5 gram of boron oxide, 1.0 gram of magnesium dichromate and 0.01 gram of beryllium oxide.

For forming the powder of third layer 24, combine 0.3 gram of sodium dichromate, 0.05 gram of silver dichromate, 0.8 gram of potassium dichromate, 0.2 gram of monocrystalline silicon powder, 0.1 gram of strontium chromate, 0.01 gram of beryllium oxide, 0.1 gram of boron oxide, 0.1 gram of sodium peroxide, 0.2 gram of β -titanium and 0.2 gram of magnesium dichromate.

Experimental

1. Introduction

Adding an appropriate quantity, on the order of several milligrams, of third layer 24 powder, which is an inorganic thermal superconductive medium to pipe, such as conduit 4, or flat interlayered piece, such as plates 36, 38, creates a superconductive device 2. For example, the addition of the third layer 24 powder into the cavity 6 of the conduit 6 or between the plates 36, 38 and then sealing the cavity 6 after subsequently eliminating the residual water and air upon heating, will create a thermal superconductive device 2. Subsequent test results prove that third layer 24 is

a superconductive medium and that a heat conducting device made of third layer 24 is a thermal superconductive heat pipe.

The fact that a conventional heat pipe shares a similar outside shape to a thermal superconductive heat pipe used to raise some misunderstandings. Therefore, it is necessary to give a brief description on the differences and similarities of the two. A convectional heat pipe makes use of the technique of liquids vaporizing upon absorbing great amounts of heat and vapors cooling upon emitting heat so as to bring the heat from the pipe's hot end to its cold end. The axial heat conducting velocity of the heat pipe depends on the value of the liquids vaporization potent heat and the circulation speed between two forms of liquid and vapor. The axial heat conducting velocity of the heat pipe also is restrained by the type and quantity of the carrier material and the temperatures and pressures at which the heat pipe operates (it can not be too high). The present superconductive heat transfer device 2 is made of a thermal superconductive medium whose axial heat conduction is accomplished by the thermal superconductive mediums' molecules high speed movement upon being heated and activated. The present superconductive heat transfer device's 2 heat conducting velocity is much higher than that of any metal bars or any convectional heat pipes of similar size, while its internal pressure is much lower than that of any convectional heat pipe of the same temperature. The applicable upper temperature limit of the present superconductive thermal heat transfer device 2 is beyond the allowed upper temperature limit of the conduit 4 material.

The present superconductive thermal heat transfer device 2 can influence most if not all categories of heat transfer, especially on the heat utilization ratio. The present superconductive thermal heat transfer device 2 also is applicable in the development and utilization of solar energy and geothermal energy, and for the recycling of lower energy level heat.

2. Testing Method And Principle

The heat conducting velocity of a metal bar depends on the bar's heat conductivity, temperature gradient and the cross-sectional area orthogonal to the temperature gradient. Metals have higher heat conductivities than nonmetal solids. Among metals, silver has the highest heat conductivity of about 415 W/mK

The present thermal superconductive heat transfer devices 2 are an entirely new development and there is no precedent as to how to exemplify and test their properties. It would appear that using the measurements of their effective or apparent heat conductivities and axial and radial heat fluxes as an indication of their properties is scientific and logical. However, this does not change the fact that no precedent is available on the measuring methods of heat conductivities of thermal superconductive devices.

The testing method used to test the properties of the present superconductive thermal heat transfer devices 2 employed an upgrade Forbes Method, in which a thermal superconductive heat pipe was taken to be a semi-infinite rod. Given that the temperature of the rod's reference surface is T_0 K, the temperature of a cross-section x meters away from the reference surface is T K, the temperature of the fluid (water) which is adjacent to the rod surface and which undergoes heat convection between itself and the rod is T_f K, the heat conductivity of the rod is k W/mK, the convectional heat transfer coefficient of the surface is h W/m²K, the girth of the rod is P meters, and the cross-sectional area of the rod is f m², the principal differential equation of heat transfer is

$$d^2T/dx^2 - (hp)/(kf)(T-T_\infty) = 0 \quad (1)$$

This is a heterogeneous differential equation. Suppose $\theta = T - T_\infty$ and Equation (1) then transforms into a homogeneous equation, by assuming $m^2 = hp/kf$, we have

$$d^2\theta/dx^2 - m^2\theta = 0 \quad (2)$$

For cylindrical objects, $m^2 = 4h/(kd_o)$, where d_o is the diameter of the cylindrical object.

5

$$\text{Suppose} \quad \theta = \theta_0 \quad \text{at } x=0 \quad (3)$$

$$\theta = 0 \quad \text{at } x=\infty \quad (4)$$

10

The solution that satisfies the above boundary conditions is

$$\theta = \theta_0 e^{-mx}$$

Under the boundary conduction defined by Equations (6) and (7)

15

$$\theta = \theta_0 \quad \text{at } x=0 \quad (6)$$

$$d\theta/dx = 0 \quad \text{at } x=L \quad (7)$$

20

then another solution of Equation (2) is

$$\theta/\theta_0 = \text{Exp}(mx) \{ [1 + \text{Exp}(2m(L-x))] / [1 + \text{Exp}(2mL)] \} \quad (8)$$

25

Since some experimental conditions may appear similar to that specified by Equations (6) and (7), and the value of the expression inside the {} is close to 1, therefore we have

$$\theta/\theta_0 = \text{Exp}(mx) \quad (9)$$

which also is correct.

The axial heat conducting velocity across the reference surface is

$$Q_x = -kf(d\theta/dx)_{x=0} \quad (10)$$

From Equation (5), we can deduce the following

$$(d\theta/dx)_{x=0} = -\theta_0 m \text{Exp}(-mx) \big|_{x=0} = -\theta_0 m$$

By substitution with Equation (6), we have

$$Q_0 = k \cdot f \cdot m \cdot \theta_0 \quad (12)$$

The speed of heat flux from rod to water is

$$Q_0 = V \cdot p \cdot C_p \cdot (T_o - T_i) \text{ watts} \quad (13)$$

where V =volume flow rate of water (m^3/s)

p =density of water (kg/m^3)

C_p =specific heat of water (J/kgK)

T_o =outlet temperature of water (K)

T_i =inlet temperature of water (K)

$$Q_i = d_o \pi L h t_{in} \quad (14)$$

where L =length of the rod (meters)

d_o =outer diameter of the rod (meters)

h =convective heat transfer coefficient (W/m^2K)

$t_{in}=(\theta_o-\theta_L)/\ln(\theta_o/\theta_L)$

5 Upon having measured the above quantities, the effective heat conductivity of a thermal superconductive heat pipe can be calculated and the heat flux also can be calculated.

10 3. Testing Apparatus

Based on the above mentioned testing principle and mathematical model, a testing apparatus, as shown in Figure 7, comprising the thermal heat conductive pipe 102, cooling water casing pipe 104, thermocouples 106, pressure gauge 108, water vapor heating chamber 110, condensed water collector 112, and evacuation valve 114 was assembled.

15 4. Testing Results

There are many advantages using saturated water vapor as the heat source to activate the thermal superconductive medium 24 inside the device 2. Saturated water vapor has a higher condensing heat transfer coefficient and the saturated water vapor comes into direct contact with the heated surface of the device 2 exclusive of contact heat resistance. Keeping the pressure of the saturated water vapor under control means keeping the heating temperature under control, and can provide the thermal superconductive heat transfer device 2 with a stable heat flux. After the flow rate and the inlet temperature of the cooling water is specified, the testing system will come into a stable equilibrium. All of the physical quantities that are measured are stable and well repeatable.

25 The following chart illustrates four representative groups of measured results, and Figures 8-11 show these results graphically.

Results of Measurement

No.	Axial Heat Flux (W/m)	Radial Heat Flux (W/m)	Effective Heat Conductivity (W/mK)	k/kAg
1	8.618×10^6	4.396×10^4	1.969×10^6	4.746×10^3
2	8.363×10^6	4.267×10^4	3.183×10^6	7.672×10^3
3	8.260×10^6	4.214×10^4	2.624×10^5	6.324×10^2
4	8.831×10^6	4.505×10^4	3.235×10^4	7.795×10^2

5 The temperature distribution curve, effective heat conductivity, convectional heat transfer coefficient of the pipe surface of the cooling segment, and heat conducting velocity were obtained under different cooling water flow rates. Although these values show certain differences, they indicate that the heat pipe is thermally superconductive.

10 Changes of cooling water flow rates causes changes in temperature distribution, but no changes in heat conducting velocity. This means that the heat conducting velocity in the heating segment has reached its upper limit. That the heat conducting area of the heating segment was designed not great enough was due to the underestimation of the heat conducting capability of the heat pipe. Changes in
15 temperature distribution brought changes in the value and sign of slope m in the correlation equation. That the convectional heat transfer coefficient was changed means that the effective heat conductivity also was changed. The thermal superconductivity of the heat pipe is confirmed by these changes. When m has a plus sign, the outlet temperature of the cooling water approaches the temperature at the
20 base of the heat pipe (at $x=0$). A conventional heat exchanger can attain such a high heat transfer efficiency only under the condition of counter flow. If the cooling water flow rate is increased, then the outlet temperature of the cooling water approaches

that at the other end ($x=L$). A conventional heat exchanger can reach such a great heat transfer efficiency only when the heat conducting area is infinite.

Therefore, the foregoing, including the examples, is considered as illustrative only of the principles of the invention. Further, various modifications may be made
5 of the invention without departing from the scope and spirit thereof and it is desired, therefore, that only such limitations shall be placed thereon as are imposed by the prior art and which are set forth in the appended claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000